

Product information

95 36 315 A

Cable Cutter

(ratchet action) For steel wire armoured cables (SWA cable) IEC 60900 DIN EN 60900

- Cuts through steel wire armoured cables up to Ø 45 mm / 380 mm² (e.g. 4 x 95 mm²) using one or two-handed operation
- Sturdy. Easy to use. Stable.
- Simple handling due to low weight (800 g) and compact design (315 mm length) can also be used in confined areas
- Precision-ground blades and induction-hardened cutting edges cut smoothly and neatly without crushing
- Innovative high leverage three-stage ratchet-drive
- Support area for putting down the pliers when cutting
- Not suitable for cutting ACSR cable and wire rope!
- Cutter head: special high-grade tool steel, forged, oil-hardened



£1000V /WM ♥

General

Article No.95 36 315 AEAN4003773078579Pliersblack lacqueredHandlesinsulated with multi-component grips, VDE-testedWeight800 gDimensions315 x 140 x 30 mmStandardIEC 60900 DIN EN 60900REACH compliantdoes not contain SVHCRoHS compliantnot applicableCutting capacity copper cable, multiple- stranded380 mm²Cutting capacity copper cable, multiple- strandedØ45 mm	Contrai	
Pliersblack lacqueredHandlesinsulated with multi-component grips, VDE-testedWeight800 gDimensions315 x 140 x 30 mmStandardIEC 60900 DIN EN 60900REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacity copper cable, multiple- strandedCutting capacity copper cable, multiple- strandedØ 45 mm	Article No.	95 36 315 A
Handlesinsulated with multi-component grips, VDE-testedWeight800 gDimensions315 x 140 x 30 mmStandardIEC 60900 DIN EN 60900REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacity copper cable, multiple- stranded380 mm²Cutting capacity copper cable, multiple- strandedØ 45 mm	EAN	4003773078579
Weight800 gDimensions315 x 140 x 30 mmStandardIEC 60900 DIN EN 60900REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacity copper cable, multiple- strandedCutting capacity copper cable, multiple- stranded380 mm²Cutting capacity copper cable, multiple- strandedØ 45 mm	Pliers	black lacquered
Dimensions315 x 140 x 30 mmStandardIEC 60900 DIN EN 60900REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacity copper cable, multiple- strandedCutting capacity copper cable, multiple- strandedØ 45 mm	Handles	insulated with multi-component grips, VDE-tested
Standard IEC 60900 DIN EN 60900 REACH compliant does not contain SVHC RoHS compliant not applicable Technical details Cutting capacity copper cable, multiple- stranded 380 mm² Cutting capacity copper cable, multiple- Ø 45 mm	Weight	800 g
REACH compliantdoes not contain SVHCRoHS compliantnot applicableTechnical detailsCutting capacity copper cable, multiple- stranded380 mm²Cutting capacity copper cable, multiple- with the strandedØ 45 mm	Dimensions	315 x 140 x 30 mm
RoHS compliant not applicable Technical details Stranded Cutting capacity copper cable, multiple-stranded 380 mm² Cutting capacity copper cable, multiple- Ø 45 mm	Standard	IEC 60900 DIN EN 60900
Technical details Cutting capacity copper cable, multiple- stranded 380 mm² Cutting capacity copper cable, multiple- Ø 45 mm	REACH compliant	does not contain SVHC
Cutting capacity copper cable, multiple- stranded 380 mm² Cutting capacity copper cable, multiple- Ø 45 mm	RoHS compliant	not applicable
stranded Cutting capacity copper cable, multiple- Ø 45 mm	Technical details	
		380 mm ²
		Ø 45 mm
MCM 750	MCM	750
VDE tested yes	VDE tested	yes

technical change and errors excepted

KNIPEX Quality – Made in Germany







Precision-milled and induction-hardened cutting edge