


## **Gripping Tweezers** Blunt tips, plastic

## 92





- > High temperature and excellent chemical resistance
- > 100% anti-magnetic
- > Blunt tips offer a firm grip but won't damage surrounding components
- > ESD handle versions discharge electrostatic energy through the handles in a gradual and controlled manner (Conductive 10<sup>2</sup>/10<sup>3</sup> OHM regarding DIN EN 61340-5-1)





92 69 84





92 09 01 ESD


## 92 09 05 ESD

	Product Number	Length	Width	Height	Finish	Style	Gripping Surface	Tip (A)	Tip (B)	Tip (C)
Boord City of C	92 69 84	5"	1/2"	1 5/16"	plastic, anti-magnetic, acid resistant	straight	serrated	3.00 mm	2.00 mm	-
LEASE 2777) (B)	92 09 01 ESD	4 1/2"	3/8"	1/2"	carbon reinforced plastic, anti-magnetic, acid resistant, ESD	straight	smooth	0.35 mm	2.00 mm	-
territor in all model (46)	92 09 04 ESD	4 1/2"	7/16"	9/16"	carbon reinforced plastic, anti-magnetic, acid resistant, ESD	straight	smooth	0.12 mm	3.30 mm	11.50 mm
Sanah 19 (Sanah (K))	92 09 05 ESD	4 1/2"	7/16"	9/16	carbon reinforced plastic, anti-magnetic, acid resistant, ESD	straight	smooth	0.12 mm	7.70 mm	11.30 mm


92


## Gripping Tweezers Pointed tips, premium stainless steel

- > Premium stainless steel resists most chemicals, salts and acids
- > Used in the chemical, pharmaceutical and electrical industries
- > 80% anti-magnetic (20% magnetic due to weld during manufacturing)
- > Pointed tips offer precise gripping of fine components
- > 92 81 02, 92 81 03, 92 81 05 have replaceable ESD tips (Conductive 10<sup>2</sup>/10<sup>3</sup> OHM regarding DIN EN 61340-5-1)









92 81 02, 92 89 02, 92 81 05 and 92 89 05

	Product Number	Length	Width	Height	Finish	Style	Gripping Surface	Tip (A)	Tip (B)
KHIPEX 52 21 01	92 21 01	4 3/4"	3/8"	1/2"	premium stainless steel, acid resistant	straight	smooth	0.50 mm	0.90 mm
NUM PROVIDENT	92 81 02	5 1/8"	3/8"	11/16"	premium stainless steel with plastic and carbon fiber replaceable tips, 80% anti-magnetic, acid resistant, ESD	straight	smooth	0.40 mm	0.60 mm
11000	92 89 02	1 1/2"	5/16"	1/8"	plastic and carbon fiber replaceable tips for 92 81 02, anti-magnetic, acid resistant, ESD	straight	smooth	0.40 mm	0.60 mm
A CONTRACTOR	92 81 03	5 1/8"	9/16"	11/16"	premium stainless steel with plastic and carbon fiber replaceable tips, 80% anti-magnetic, acid resistant, ESD	60° angled	smooth	0.40 mm	0.70 mm
- Constant	92 89 03	1 1/2"	9/16"	1/8"	plastic and carbon fiber replaceable tips for 92 81 03, anti-magnetic, acid resistant, ESD	60° angled	smooth	0.40 mm	0.70 mm
and the second second	92 81 05	5 1/8"	3/8"	11/16"	premium stainless steel with plastic and carbon fiber replaceable tips, 80% anti-magnetic, acid resistant, ESD	straight	smooth	0.70 mm	0.60 mm
Marca .	92 89 05	1 1/2"	5/16"	1/8"	plastic and carbon fiber replaceable tips for 92 81 05, anti-magnetic, acid resistant, ESD	straight	smooth	0.70 mm	0.60 mm