- > for single, multi and fine-stranded wire cables with plastic or rubber insulation; especially useful with THHN coated wire
- > adapts automatically to the respective cable diameter preventing damage to the conductor
- > cutting depth can be adjusted for different insulation by turning the red wheel
- > includes wire cutter for copper and aluminum wires, multi-stranded up to 8 AWG (10 mm²) and single stranded up to 10 AWG (6 mm²)
- > smooth operating mechanism
- > replaceable blade and plastic clamping jaws
- > the body is constructed of lightweight fiberglass-reinforced plastic
- > blade: special tool steel; oil-hardened



12 40 200

For thin ribbon cables up to 10 mm width in a single pass



12 40 200: Adjustable length stop



12 40 200: Precise stripping prevents damage to the conductor



Wire cutter for multi-stranded wire cables up to 8 AWG (10 $\,$ mm 2)



12 40 200 X 8 200 MM 0.03 - 10.0 32 - 8 1/8 - 11/16 3.0 - 18.0 0.45 12 50 200 8 200 MM 2.5 - 16.0 14 - 6 - 0.44	Product Number	Packaging	←→ Inch mm		Stripping capacities mm ²	AWG	Length stop Inch mm	∆¹∆ Ibs
12 50 200 1 1/ ₂ 6 1 1/ ₂	12 40 200	X	_	MM	0.03 - 10.0	32 - 8		0.45
	12 50 200			MM	2.5 - 16.0	14 - 6	-	0.44

12 49 01	1 pair of spare blades for 12 40 200				
12 49 02	1 pair of spare clamping jaws for 12 40 200				
12 49 03	Spare length stop for 12 40 200				
12 59 01	1 pair of spare blades for 12 50 200				
12 59 02	1 pair of spare clamping jaws for 12 50 200				