- > for copper and aluminum cables, single and multi-stranded wire also with hard rubber, plastic sheet metal sheath
- > not suitable for steel wire and wire ropes
- > minimal handforce required for cutting due to optimum transmission ratio
- > high cutting capacity due to two-handed operation and ratchet action
- > the blade can be opened in any cutting position
- > adjust the handle length to adapt to each individual job and move it to the shorter length for easy transport
- > blade: special-quality high-grade tool steel, oil-hardened
- > handles: high-strength oval aluminum tubing

95 32 060

Tool length: 23 5/8" - 31 1/2" (600 - 800 mm)

95 32 100

Tool length: 25 1/2" - 33 7/8" (650 - 850 mm)



95 32 060

WARNING: This product can expose you to chemicals including Diisononyl Phthalate, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Product Number	Packaging	←→ Inch mm		Head	Handles	Cutting capacities			
						Ø Inch Ø mm	mm²	MCM	∆ ∆ lbs
95 32 060		23 5/8 - 31 1/2 600 - 800		burnished	multi-component grips	2 3/64 60	740	1400	8.47
95 32 100		25 1/2 - 33 7/8 650 - 850 mm	•			3 15/16 100	960	1900	10.98
95 39 720	Movable spare blade for 95 32 060								
95 39 870	Movable spare blade for 95 32 100								

