









Wire ferrules-Overview table

Dimensional tolerances According to DIN 46228 part 4	Description + Technical information	Art.No	EAN 4003773-	Colour code DIN 46228/4	Size mm ²	L1	L2	d1	d2	S1	S2	d3	Packing unit	
 	Insulated single ferrules Insertion Funnel is made of Polypropylene and is heatresistant up to 105 Deg. C, Material: E-Copper, Surface electro tinned, Minimum Coating Thickness 3µm	97 99 330	076414	○	0,50	14,00	8,00	1,00	2,60	0,15	0,25		200	
		97 99 331	076421	●	0,75	14,00	8,00	1,20	2,80	0,15	0,25		200	
		97 99 332	076438	●	1,00	14,00	8,00	1,40	3,00	0,15	0,25		200	
		97 99 333	076445	●	1,50	14,00	8,00	1,70	3,50	0,15	0,25		200	
		97 99 334	076452	●	2,50	14,00	8,00	2,20	4,20	0,15	0,25		200	
		97 99 335	076469	●	4,00	17,00	10,00	2,80	4,80	0,20	0,30		200	
		97 99 336	076476	●	6,00	20,00	12,00	3,50	6,30	0,20	0,30		100	
		97 99 337	076483	●	10,00	22,00	12,00	4,50	7,60	0,20	0,40		100	
		97 99 338	076490	●	16,00	24,00	12,00	5,80	8,80	0,20	0,40		100	
		97 99 339	076506	●	25,00	30,00	16,00	7,30	11,20	0,20	0,40		50	
 	Insulated single ferrules (long version) Insertion Funnel is made of Polypropylene and is heatresistant up to 105 Deg. C, Material: E-Copper, Surface electro tinned, Minimum Coating Thickness 3µm	97 99 350	076513	○	0,50	16,00	10,00	1,00	2,60	0,15	0,25		200	
		97 99 351	076520	●	0,75	16,00	10,00	1,20	2,80	0,15	0,25		200	
		97 99 352	076537	●	1,00	16,00	10,00	1,40	3,00	0,15	0,25		200	
		97 99 353	076544	●	1,50	16,00	10,00	1,40	3,50	0,15	0,25		200	
		97 99 354	076551	●	2,50	18,00	12,00	2,20	4,20	0,15	0,25		200	
		97 99 355	076568	●	4,00	20,00	12,00	2,80	4,80	0,20	0,30		200	
		97 99 356	076575	●	6,00	26,00	18,00	3,50	6,30	0,20	0,30		100	
		97 99 357	076582	●	10,00	28,00	18,00	4,50	7,60	0,20	0,40		100	
		97 99 358	076599	●	16,00	28,00	18,00	5,80	8,80	0,20	0,40		100	
		97 99 359	076605	●	25,00	32,00	18,00	7,30	11,20	0,20	0,40		50	
 	Insulated twin ferrules Insertion Funnel is made of Polypropylene and is heatresistant up to 105 Deg. C, Material: E-Copper, Surface electro tinned, Minimum Coating Thickness 3µm	97 99 370	076612	○	2 x 0,50	15,00	8,00	1,40	2,50	0,15	0,25	4,70	200	
		97 99 371	076629	●	2 x 0,75	15,00	8,00	1,70	2,80	0,15	0,25		5,00	200
		97 99 372	076636	●	2 x 1,00	15,00	8,00	1,95	3,40	0,15	0,30		5,40	200
		97 99 373	076643	●	2 x 1,50	16,00	8,00	2,20	3,60	0,15	0,30		6,60	200
		97 99 374	076650	●	2 x 2,50	18,50	10,00	2,80	4,20	0,20	0,30		7,80	100
		97 99 375	076667	●	2 x 4,00	23,00	12,00	3,70	4,90	0,20	0,40		8,80	100
		97 99 376	076674	●	2 x 6,00	26,00	14,00	4,80	6,90	0,20	0,40		10,00	50
		97 99 377	076681	●	2 x 10,00	26,00	14,00	6,40	7,20	0,20	0,40		13,00	50
		97 99 378	076698	●	2 x 16,00	30,00	14,00	8,20	9,60	0,20	0,40		18,40	25
		 	Uninsulated ferrules Material: E-Copper, Surface electro tinned, Minimum Coating Thickness 3µm	97 99 390	076704		0,50	6,00		1,00	2,10	0,15		
97 99 391	076711				0,75	6,00		1,20	2,30	0,15				200
97 99 392	076728				1,00	6,00		1,40	2,50	0,15				200
97 99 393	076735				1,50	7,00		1,70	2,80	0,15				200
97 99 394	076742				2,50	7,00		2,20	3,40	0,15				200
97 99 395	076759				4,00	9,00		2,80	4,00	0,20				200
97 99 396	076766				6,00	12,00		3,50	4,70	0,20				100
97 99 397	076773				10,00	12,00		4,50	5,80	0,20				100
97 99 398	076780				16,00	12,00		5,80	7,50	0,20				100
97 99 399	076797				25,00	12,00		7,30	9,50	0,20				50